



DATE BY	REVISION
89/9.6	△

MAT'L:
 1.CABLE:UL2919,3COAXIAL+7C+1+AL/MY+BRAID,O.D:8.5
 2.CONNECTORS:HD15M,9th EMPTY,BLACK
 HD15F,BLACK
 3.THUMBSCREW:#4-40UNC,E32
 4.BLACK HEAT SHRINK:Ø1.5 X 15:6PCS
 Ø3 X 8:6PCS
 5.COPPER SIZE:30 X 50
 NOTE:
 1.TOTAL LENGTH:5000±50mm
 2.COLOR:BEIGE
 3.MOLDED TYPE
 4.360° SOLDER

CONFIGURATION:

HD15M		HD15F
1	RED(COAX.)	1
6	RED(GROUND)	6
2	GREEN(COAX.)	2
7	GREEN(GROUND)	7
3	BLUE(COAX.)	3
8	BLUE(GROUND)	8
4	BROWN	4
5	BLACK	5
	GREEN	
13	RED	13
14	ORANGE	14
10	WHITE	10
11	YELLOW	11
12	(BRAID)	12
SHIELD		SHIELD

④	THUMBSCREW:#4-40UNC,E32	4
③	#28,UL2919,3COAX+7C+1+AL/MY+B,O.D:8.5	5M
②	HD15F,BLACK	1
①	HD15M,9th EMPTY,BLACK	1
NO.	DESCRIPTION	QTY

△ *MODIFY:DESIGNATE INNER CORD COLOR(M00089) Y.C.C/89.9.6

DATE	18 JUN,1998	PARTS NO	MN3073N	TITLE:	HD15 MALE-HD15 FEMALE (MOLDED TYPE)	DRAWN	Y.C.C 6/18	CHECK		APPRO	
UNIT	MM	DRAWN NO	001131			ASSMANN ELECTRONICS.INC					
SCALE		BUYER NO	002		AK3740X 5M						