



TAPE MOUNTED
-2 ONLY

1. WIRE BARREL WILL ACCEPT #22-28 AWG WIRE.
2. CRIMPING TOOL - USE HAND TOOL M22520/2-01 (AMP P/N 601966-1) WITH POSITIONER M22520/2-06 (AMP P/N 601966-4). SEE AMP INSTRUCTION SHEET, IS7516, FOR CRIMPING INSTRUCTIONS.
3. CONTACT QUALIFIED TO NASA P/N G-08-S1.
4. INSERTION/EXTRACTION TOOL AMP P/N 91067-1.
5. USE AMP - TAPOMATIC STRIPPER/CRIMPER MACHINE NUMBER 599406-7 WITH FUNNEL NUMBER 125905-2.
6. SLEEVE MAY BE CRIMPED OR DIMPLED TO BODY.
7. PLATING: GOLD PER ASTM-B-488 (TYPEII) OVER NICKEL PER QQ-N-290.
8. PLATING: GOLD PER ASTM-B-488 (TYPEII) OVER COPPER PER MIL-C-14550, CLASS 4.

2	AS SHOWN	3	206071-4
5	CONTACT ON TAPE	SAME AS -1	206071-2
2	AS SHOWN	8	206071-1
REMARKS	DESCRIPTION	FINISH	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN T. THOMPSON 06-03-94	
DIMENSIONS: INCHES		CHK F. KINSEY 06-03-94	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		AP'D F. KINSEY 06-03-94	
0 PLC	± .005	NAME	
1 PLC	± .005	CONTACT ASSEMBLY, SOCKET, SIZE 22D	
2 PLC	± .005	APPLICATION SPEC	
3 PLC	± .005	SIZE	
4 PLC	± .005	CAGE CODE	
ANGLES	± .005	DRAWING NO	
MATERIAL SEE CALLOUT	FINISH SEE TABLE	WEIGHT 102 GRAMS	RESTRICTED TO
		A1 00779	SCALE 20:1 SHEET 1 OF 1 REV H1